

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product form: Mixture

Product name: AeroSpot™

Product code: AeroSpot Blue (E&I 30 4), AeroSpot Red (E&I 30 5), AeroSpot Black (E&I 30 8), AeroSpot White (E&I 30 3), AeroSpot Yellow LF (E&I 30 13), AeroSpot Orange LF (E&I 30 14), AeroSpot Dark Blue (E&I 62 42), AeroSpot Dark Green (E&I 62 45), AeroSpot Gray (E&I 62 49), AeroSpot Blue Glo (E&I 31 42-FL), AeroSpot Orange Glo (E&I 30 11), AeroSpot Green Glo (E&I 30 12), AeroSpot Pink Glo (E&I 31 48-FL), AeroSpot Red Glo (E&I 31 46-FL), AeroSpot Light Green (E&I 30 9), AeroSpot Purple (E&I 30 16)

1.2. Intended Use Of The Product

Use of the substance/preparation: Tree and log marking paint

1.3. Name, Address, And Telephone Of The Responsible Party

Company

The Nelson Paint Company
One Nelson Drive
Kingsford, MI 49802
906-774-5567

Importer

The Nelson Paint Company of Canada
48 Industrial Park Crescent
Sault Ste Marie Ontario, P6B 5P2
705-459-4680

1.4. Emergency telephone number

Emergency number : In US and Canada CHEMTEL: 1-800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Flam. Liq. 2 H225
Eye Irrit. 2B H320
Skin Sens. 1 H317
Muta. 1B H340
Carc. 1A H350
Repr. 1B H360
STOT SE 1 H370
STOT SE 3 H336
STOT RE 1 H372

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H222 - Extremely flammable aerosol
H225 - Highly flammable liquid and vapor
H317 - May cause an allergic skin reaction
H320 - Causes eye irritation
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects
H350 - May cause cancer
H360 - May damage fertility or the unborn child
H370 - Causes damage to organs
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US)

: P201 - Obtain special instructions before use

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 - Do not spray on an open flame or other ignition source
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P251 - Pressurized container: do not pierce or burn, even after use
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: get medical advice/attention
P312 - Call a POISON CENTER or doctor if you feel unwell
P314 - Get medical advice and attention if you feel unwell.
P321 - Specific treatment (see Section 4)
P333+P313 - If skin irritation or rash occurs: get medical advice/attention
P337+P313 - If eye irritation persists: get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use appropriate media for extinction. See Section 5.
P233 - Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents/container according to local, regional, national, and international regulations.

2.3. Other hazards

Other hazards not contributing to the classification: In the final product, 0.02 gallons of propane gas (CAS # 74-98-6) is added to the can and acts as an aerosol propellant. Propane gas classification (GHS-US): Simple Asphyxiant, Flammable Gas Category 1 (H220), Compressed Gas (H280), STOT SE 3 (H336).

2.4. Unknown acute toxicity (GHS US)

2.5% of the mixture consists of ingredients of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification (GHS-US)
Mineral Spirits	(CAS No.) 8052-41-3	26.8 - 32.76	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Methyl alcohol	(CAS No.) 67-56-1	8.79 - 10.39	Flam. Liq. 2, H225 Eye Irrit. 2B, H320 Repr. 1B, H360 STOT SE 3, H335

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

			STOT SE 1, H370 STOT RE 1, H372
Titanium dioxide	(CAS No.) 13463-67-7	0 - 9.9862	Skin Irrit. 2, H315 Carc. 2, H351
Sodium chloride	(CAS No.) 7647-14-5	0 - 2.8775	Eye Irrit. 2A, H319
Iron oxide yellow	(CAS No.) 51274-00-1	0 - 1.64	STOT SE 3, H335 STOT RE 1, H372
Copper, [1,2,3,4,8,9,10,11,15,16,17,18,22,23,24,25-hexadecachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]-, (SP-4-1)-	(CAS No.) 14832-14-5	0 - 1.209	Repr. 2, H361
Carbon black	(CAS No.) 1333-86-4	0 - 1.12	Carc. 2, H351 STOT SE 3, H335
Aluminum hydroxide	(CAS No.) 21645-51-2	0 - 0.9171	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Barium sulfate	(CAS No.) 7727-43-7	0 - 0.758	STOT SE 3, H336 STOT RE 2, H373
Stoddard solvent	(CAS No.) 8052-41-3	0.028 - 0.5748	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Methyl ethyl ketoxime	(CAS No.) 96-29-7	0 - 0.45	Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
1,2-Propylene glycol	(CAS No.) 57-55-6	0 - 0.21	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
Quartz	(CAS No.) 14808-60-7	0.0309 - 0.1788	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Cobalt naphthenate	(CAS No.) 61789-51-3	0 - 0.11	Carc. 2, H351

Additional Information: In the final product, 0.02 gallons of propane gas (CAS # 74-98-6) is added to the can and acts as an aerosol propellant. **Carbon black (1333-86-4)** is only present in the Aero Spot Black (E&I 30 8) and Aero Spot Grey (E&I 62 49) formulations. **Cobalt naphthenate (61789-51-3)** is present only in the Aero Spot Blue-Glo (E&I 31 42-FL) formulation.

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general: If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact: Gently wash with plenty of soap and water. If skin irritation or rash occurs: get medical advice/attention.

First-aid measures after eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries: May damage fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure. May cause genetic defects.

Symptoms/injuries after inhalation: May cause cancer by inhalation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact: May cause an allergic skin reaction. May cause mild skin irritation.

Symptoms/injuries after eye contact: May cause eye irritation.

Symptoms/injuries after ingestion: May be harmful if swallowed.

Chronic symptoms: Prolonged and frequent exposure through inhalation may cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard: Highly flammable liquid and vapor. Extremely flammable aerosol.

Explosion hazard: May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for firefighters

Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid all eye and skin contact and do not breathe vapor and mist.

6.1.1. For non-emergency personnel

Protective equipment: Use appropriate personal protection equipment (PPE).

Emergency procedures: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment: Use appropriate personal protection equipment (PPE).

Emergency procedures: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for cleaning up: Clear up spills immediately and dispose of waste safely.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed: Handle empty containers with care because residual vapors are flammable. Pressurized container: do not pierce or burn, even after use.

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.

Handling temperature: ≤ 50 °C (122 °F)

Hygiene measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures: Prevent build-up of electrostatic charges (e.g., by grounding). Comply with applicable regulations.

Storage conditions: Do not expose to temperatures exceeding 122°F (50°C). Keep only in the original container in a cool, well ventilated place away from heat, direct sunlight, sparks, open flame, ignition sources. Store locked up.

Incompatible products: Strong bases. Strong acids.

Storage temperature: ≤ 50 °C (122 °F)

7.3. Specific end use(s)

Tree and log marking paint.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon black (1333-86-4)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
Titanium dioxide (13463-67-7)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
Methyl alcohol (67-56-1)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Limestone (1317-65-3)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Stoddard solvent (8052-41-3)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Barium sulfate (7727-43-7)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Kaolin (1332-58-7)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Propane (74-98-6)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

Appropriate engineering controls

: Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

: Dust/aerosol mask. Protective clothing. Gloves. Safety glasses.



Hand protection

: Wear protective gloves.

Eye protection

: Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other information

: When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol spray paint
Odor	: Slight solvent smell
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: < 1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 150 - 205 °C (302-401 °F)
Flash Point	: No data available
Auto-ignition temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: 414 - 483 kPa
Relative vapor density at 20 °C	: > 1 (air=1)
Relative density	: 0.98 - 1.1
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

VOC content : 50.3 - 64 (% by weight)

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Formation of toxic gases is possible during heating or fire. May include oxides of carbon, nitrogen and products of chlorine.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Carbon black (1333-86-4)	
LD50 oral rat	> 15400 mg/kg
LD50 dermal rabbit	> 3 g/kg
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
Quartz (14808-60-7)	
LD50 oral rat	> 5000 mg/kg
Methyl ethyl ketoxime (96-29-7)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	0.2 mg/kg
LC50 inhalation rat (mg/l)	20 mg/l (Exposure time: 4 h)
Methyl alcohol (67-56-1)	
LD50 oral rat	5628 mg/kg
LD50 dermal rabbit	15800 mg/kg
LC50 inhalation rat (mg/l)	83.2 mg/l (Exposure time: 4 h)
LC50 inhalation rat (ppm)	64000 ppm (Exposure time: 4 h)
1,2-Propylene glycol (57-55-6)	
LD50 oral rat	20000 mg/kg
LD50 dermal rabbit	20800 mg/kg
Aluminum hydroxide (21645-51-2)	
LD50 oral rat	> 5000 mg/kg
Silica, amorphous (7631-86-9)	
LD50 oral rat	> 5000 mg/kg

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 2.2 mg/l (Exposure time: 1 h)
Manganese naphthenate (1336-93-2)	
LD50 oral rat	> 6 g/kg
Stoddard solvent (8052-41-3)	
LD50 oral rat	> 5 g/kg Behavioral somnolence
LD50 dermal rabbit	> 3 mg/kg
Calcium propionate (4075-81-4)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	500 mg/kg
LC50 inhalation rat (mg/l)	> 19.7 mg/l (Exposure time: 1 h)
Diethylene glycol monomethyl ether (111-77-3)	
LD50 oral rat	4 ml/kg
LD50 dermal rabbit	2500 µl/kg
Propylene glycol monomethyl ether (107-98-2)	
LD50 oral rat	5200 mg/kg
LD50 dermal rabbit	13000 mg/kg
LC50 inhalation rat (mg/l)	> 24 mg/l (Exposure time: 1 h)
Sodium chloride (7647-14-5)	
LD50 oral rat	3 g/kg
LD50 dermal rabbit	> 10 g/kg
LC50 inhalation rat (mg/l)	> 42 g/m ³ (Exposure time: 1 h)
Cobalt naphthenate (61789-51-3)	
LD50 oral rat	3900 mg/kg
Ferrate(4-), hexakis(cyano-C)-, ammonium iron(3+) (1:1:1), (OC-6-11)- (25869-00-5)	
LD50 oral rat	> 5000 mg/kg
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (136-52-7)	
LD50 oral rat	1.22 g/kg
Quinacridone magenta (980-26-7)	
LD50 oral rat	> 23 g/kg
LD50 dermal rabbit	> 3 g/kg
Propane (74-98-6)	
LC50 inhalation rat (mg/l)	658 mg/l (Exposure time: 4 h)

Skin corrosion/irritation: Not classified.

Eye damage/irritation: Causes eye irritation.

Respiratory or skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Carbon black (1333-86-4)	
IARC group	2B
Titanium dioxide (13463-67-7)	
IARC group	2B
National Toxicity Program (NTP) Status	1
Quartz (14808-60-7)	
IARC group	1
National Toxicity Program (NTP) Status	2
Silica, amorphous (7631-86-9)	
IARC group	3
Cobalt naphthenate (61789-51-3)	
IARC group	2B

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

C.I. Pigment Red 3 (2425-85-6)	
IARC group	3
National Toxicity Program (NTP) Status	1

Reproductive toxicity: May damage fertility or the unborn child.

Specific target organ toxicity (single exposure): Causes damage to organs. May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard: Not classified

Symptoms/injuries after inhalation: May cause cancer by inhalation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact: May cause an allergic skin reaction. May cause mild skin irritation.

Symptoms/injuries after eye contact: May cause eye irritation.

Symptoms/injuries after ingestion: May be harmful if swallowed.

Chronic symptoms: Prolonged and frequent exposure through inhalation may cause cancer.

SECTION 12: Ecological information

12.1. Toxicity

Carbon black (1333-86-4)	
EC50 Daphnia 1	> 5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)
Methyl ethyl ketoxime (96-29-7)	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	83 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
LC50 fish 2	320 - 1000 mg/l (Exposure time: 96 h - Species: Leuciscus idus [static])
Methyl alcohol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
1,2-Propylene glycol (57-55-6)	
LC50 fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	> 10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	19000 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	41 (41 - 47) ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Silica, amorphous (7631-86-9)	
LC50 fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
EC50 other aquatic organisms 1	440 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
Calcium propionate (4075-81-4)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Leuciscus idus [static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 500 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
Diethylene glycol monomethyl ether (111-77-3)	
LC50 fish 1	7500 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 500 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
Propylene glycol monomethyl ether (107-98-2)	
LC50 fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4600 - 10000 mg/l (Exposure time: 96 h - Species: Leuciscus idus [static])
C.I. Pigment Blue 15 (147-14-8)	
LC50 fish 1	> 100 mg/l (Exposure time: 48 h - Species: Oryzias latipes [static])
Sodium chloride (7647-14-5)	
LC50 fish 1	5560 - 6080 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	12946 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	340.7 - 469.2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Ferrate(4-), hexakis(cyano-C)-, ammonium iron(3+) (1:1:1), (OC-6-11)- (25869-00-5)	
LC50 fish 1	> 1000 mg/l (Exposure time: 96 h - Species: Leuciscus idus [semi-static])

12.2. Persistence and degradability

AeroSpot™	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

AeroSpot™	
Bioaccumulative potential	Not established.
Methyl ethyl ketoxime (96-29-7)	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)
Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77
1,2-Propylene glycol (57-55-6)	
BCF fish 1	< 1
Silica, amorphous (7631-86-9)	
BCF fish 1	(no bioaccumulation expected)
Stoddard solvent (8052-41-3)	
Log Pow	3.16 (Octanol/water partition coefficient 3.16/7.06)
Diethylene glycol monomethyl ether (111-77-3)	
Log Pow	-0.682
Propylene glycol monomethyl ether (107-98-2)	
BCF fish 1	< 2
Log Pow	-0.437
C.I. Pigment Blue 15 (147-14-8)	
BCF fish 1	0.3 - 11
Log Pow	6.6 (at 25 °C)
Sodium chloride (7647-14-5)	
BCF fish 1	(no bioaccumulation)
Propane (74-98-6)	
Log Pow	2.3

12.4. Mobility in soil No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional information: Handle empty containers with care because residual vapors are flammable. Container under pressure. Do not drill or burn even after use.

Ecology - waste materials: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ICAO/IATA/DOT/TDG

14.1. UN number

UN-No.(DOT) : 1950
DOT NA no. UN1950

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols
flammable, (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas.



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

SECTION 15: Regulatory information

15.1. US Federal regulations

Carbon black (1333-86-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Methyl ethyl ketoxime (96-29-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Methyl alcohol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 %
Copper, [1,2,3,4,8,9,10,11,15,16,17,18,22,23,24,25-hexadecachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]-, (SP-4-1)- (14832-14-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Iron oxide yellow (51274-00-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Soybean oil, polymer with Isophthalic acid and Pentaerythritol (66071-86-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Soybean lecithin (8002-43-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Tall oil fatty acids, ethoxylated (61791-00-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2-Propylene glycol (57-55-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
Aluminum hydroxide (21645-51-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Silica, amorphous (7631-86-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Manganese naphthenate (1336-93-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-Ethylhexanoic acid, manganese salt (15956-58-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Stoddard solvent (8052-41-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Zirconium ethyl hexoate (22464-99-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Calcium 2-ethylhexanoate (136-51-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Calcium neodecanoate (27253-33-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Calcium propionate (4075-81-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Diethylene glycol monomethyl ether (111-77-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Propylene glycol monomethyl ether (107-98-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
C.I. Pigment Blue 15 (147-14-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Linseed oil (8001-26-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
C.I. Acid Yellow 23 (1934-21-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium chloride (7647-14-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cobalt neodecanoate (27253-31-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cobalt naphthenate (61789-51-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ferrate(4-), hexakis(cyano-C)-, ammonium iron(3+) (1:1:1), (OC-6-11)- (25869-00-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (136-52-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Barium sulfate (7727-43-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Pigment yellow 74 (6358-31-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
D and C Orange No. 17 (3468-63-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quinacridone magenta (980-26-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
C.I. Pigment Red 3 (2425-85-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Butanamide, 2-[(4-methoxy-2-nitrophenyl)azo]-N-(2-methoxyphenyl)-3-oxo- (6528-34-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Kaolin (1332-58-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Propane (74-98-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.3. US State regulations

AeroSpot™()	
State or local regulations	This product contains a component that was manufactured with formaldehyde, which may release trace amounts of formaldehyde gas in the final product application. Formaldehyde is known to the State of California to cause cancer.
Carbon black (1333-86-4)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Methyl alcohol (67-56-1)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
D and C Orange No. 17 (3468-63-1)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Carbon black (1333-86-4)	
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Hawaii - Occupational Exposure Limits - STELs	
U.S. - Hawaii - Occupational Exposure Limits - TWAs	
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations	
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)	
U.S. - Idaho - Occupational Exposure Limits - TWAs	
U.S. - Illinois - Toxic Air Contaminant Carcinogens	
U.S. - Illinois - Toxic Air Contaminants	
U.S. - Maine - Chemicals of High Concern	
U.S. - Massachusetts - Right To Know List	
U.S. - Michigan - Occupational Exposure Limits - TWAs	
U.S. - Minnesota - Chemicals of High Concern	
U.S. - Minnesota - Hazardous Substance List	

U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Titanium dioxide (13463-67-7)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Hawaii - Occupational Exposure Limits - STELs
U.S. - Hawaii - Occupational Exposure Limits - TWAs
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Quartz (14808-60-7)

U.S. - Hawaii - Occupational Exposure Limits - TWAs
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - Oregon - Permissible Exposure Limits - Mineral Dusts
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Methyl ethyl ketoxime (96-29-7)

U.S. - Minnesota - Hazardous Substance List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Methyl alcohol (67-56-1)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Volatile Substances
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Hawaii - Occupational Exposure Limits - Skin Designations
U.S. - Hawaii - Occupational Exposure Limits - STELs
U.S. - Hawaii - Occupational Exposure Limits - TWAs
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - Skin Designations
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Iron oxide yellow (51274-00-1)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Tall oil fatty acids, ethoxylated (61791-00-2)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

1,2-Propylene glycol (57-55-6)

U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Aluminum hydroxide (21645-51-2)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Silica, amorphous (7631-86-9)

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Oregon - Permissible Exposure Limits - Mineral Dusts
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - Effects Screening Levels - Short Term
Limestone (1317-65-3)
U.S. - Hawaii - Occupational Exposure Limits - STELs U.S. - Hawaii - Occupational Exposure Limits - TWAs U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs
2-Ethylhexanoic acid, manganese salt (15956-58-8)
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Stoddard solvent (8052-41-3)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Hawaii - Occupational Exposure Limits - TWAs U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Chemicals of High Concern U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Occupational Exposure Limits - TWAs U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
Zirconium ethyl hexoate (22464-99-9)
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Calcium 2-ethylhexanoate (136-51-6)
U.S. - Texas - Effects Screening Levels - Long Term

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - Effects Screening Levels - Short Term
Calcium neodecanoate (27253-33-4)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Calcium propionate (4075-81-4)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Diethylene glycol monomethyl ether (111-77-3)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Propylene glycol monomethyl ether (107-98-2)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Hawaii - Occupational Exposure Limits - STELs
U.S. - Hawaii - Occupational Exposure Limits - TWAs
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
C.I. Pigment Blue 15 (147-14-8) U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Linseed oil (8001-26-1) U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Sodium chloride (7647-14-5) U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Cobalt neodecanoate (27253-31-2) U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Cobalt naphthenate (61789-51-3) U.S. - Illinois - Toxic Air Contaminant Carcinogens U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Ferrate(4-), hexakis(cyano-C)-, ammonium iron(3+) (1:1:1), (OC-6-11)- (25869-00-5) U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (136-52-7) U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Barium sulfate (7727-43-7) U.S. - Hawaii - Occupational Exposure Limits - TWAs U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs
Pigment yellow 74 (6358-31-2) U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
D and C Orange No. 17 (3468-63-1) U.S. - Maine - Chemicals of High Concern U.S. - Minnesota - Chemicals of High Concern U.S. - Texas - Effects Screening Levels - Long Term

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - Effects Screening Levels - Short Term
C.I. Pigment Red 3 (2425-85-6)
U.S. - Maine - Chemicals of High Concern U.S. - Minnesota - Chemicals of High Concern U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Butanamide, 2-[[4-methoxy-2-nitrophenyl]azo]-N-(2-methoxyphenyl)-3-oxo- (6528-34-3)
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Kaolin (1332-58-7)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
Propane (74-98-6)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Hawaii - Occupational Exposure Limits - TWAs U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2 U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New Jersey - Environmental Hazardous Substances List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List

U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

SECTION 16: Other information

Data sources : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Simple Asphy.	Simple Asphyxiant
Skin Irrit. 2	skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation

AeroSpot™

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure

The Nelson paint Company, Inc (TNPC) expressly disclaims all expressed or implied warranties of merchantability and fitness for particular purpose, with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, TNPC makes no representations as to its accuracy or sufficiency. Conditions of use are beyond TNPC's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

SDS US (GHS HazCom)