

NCP

NCP Coatings Inc.

Bark-Mark W/R TMP**Water Reducible Tree Marking Paint****TECHNICAL**

Intended Uses: Tree and lumber marking.

PRODUCT INFORMATION

Color:	8 standard colors	Theoretical Coverage:	N/A
Gloss:	Flat	Salt Spray Test:	N/A
Volume Solids:	7.0%	Humidity Test:	N/A
Weight Solids:	13.0%	Weatherometer Test:	Passes 700 hours QUV
Weight per Gallon:	7.8-8.2 lbs/gal	Pencil Hardness:	N/A
VOC:	5-6 lbs/gal minus water	Viscosity:	400-600 CPS
Film Thickness:	10-12 mils wet; 1-1.5 mils dry		

APPLICATION INFORMATION

Methods:	Tree marking guns, conventional or airless spray, brush
Mix Ratio:	Shake cans for 15-30 seconds before using
Reducer:	No reducing required
Cleaner:	Water clean up for wet paint, thinner for dry paint
Pot Life:	Stable for one (1) year in closed containers
Dry Time:	Air dry 30 minutes
Time To Recoat:	N/A

SURFACE PREPARATION

None required; Apply over dry bark or lumber.

SAFETY INFORMATION

Consult the Material Safety Data Sheet prior to application for detailed information on the health and safety hazards.

CAUTION: This Product is for Industrial use Only!

STORAGE

This product must be stored in accordance with local, state, and national regulations. Preferred storage conditions: Keep containers in a dry space with adequate ventilation. The containers should be tightly sealed. Handle with care. Stir well before use. Shelf life is 12 months from date of manufacture.

DRY TIME / CURE

Dry time ranges from 30-45 minutes depending on the relative humidity and outdoor temperature.

COMMENTS

These products will not freeze at 0°F.

NOTE: The above information is supplied as a guideline to our customers. The user must be aware of the cleaning, pretreatment, application and testing requirements for their specific job!

225 Fort
Street, Niles,
MI. 49120
Phone:
(800)
627-1948
(616)
683-3377
Fax:
(616)
683-3305